

PLEXIGLAS FLOWMETERS FOR SMALL FLOW RATES TYPE AM

CHARACTERISTICS

- Employment: Liquid or gas
- Accuracy: $\pm 5\%$ del f.s.v.
- Maximum pressure: 10 bar
- Maximum temperature: 70°C
- Connections material: brass, AISI 304 or AISI 316
- Brass, AISI 304 or AISI 316 needle valve

OPTIONALS

- Photoelectric cell FP/1 for min or max or FP/3 for min and max alarm
- Hose connection
- Output needle valve
- Axial version
- Reinforced version PN 25, PN 40 and PN 64



Standard rates for water 20°C or Air at atmospheric pressure

TYPE	A	B	fil. C gas	I	Construction	WATER L/h max	AIR NL/min P.A. max
a/m-95	95	30	1/4" - 3/8"	65	1 · 2 · 3	40	15
a/m-105	105	30	1/4" - 3/8"	75	1 · 2 · 3	40	30
a/m-120	120	30	1/4" - 3/8"	90	1 · 2 · 3	50	35
a/m-145	145	30	1/4" - 3/8"	115	1 · 2 · 3	120	50
a/m-185	185	30	1/4" - 3/8"	155	1	150	80

The rates are indicative, it's possible to supply different scale for specific needful

