

FLOWMETER FOR MEDIUM FLOWRATE TYPE RR / PLR

CHARACTERISTICS

- Employments: clean liquids or gases
- Precision: $\pm 5\%$ fs.
- Maximum working pressure: 10 bar
- Maximum working temperature: 70°C
- Connections and Flow regulator: Brass, AISI 304, AISI 316
- input flow regulator

ACCESSORIES

- Inductive Proxy PNP, FP/1 or FP/3 for min and max flow alarm
- output flow regulator



Standard rates for water 20°C or Air at atmospheric pressure

TYPE	Standard Flowrate		Threads Connection			
	WATER	AIR				
	L/h	Nm3/h	G	L	I	C
R-1/R	120	6	3/8" - 1/2"	160	115	40
	200					
	300	8				
	400					
	500	10				
R-2/R	600	15	3/8" - 1/2"	190	140	45
	800					
	1200	25				
	1500					
	2000					

TYPE	Standard flowrate		Threads Connection			
	WATER	AIR				
	L/h	Nm3/h	G	L	I	C
PL-1/R	120	6	3/8" - 1/2"	215	170	40
	200					
	300	8				
	400					
	500	10				
PL-2/R	600	15	3/8" - 1/2"	255	205	45
	800					
	1200	25				
	1500					
	2000					

The rates are indicative, it's possible to supply different scale for specific needful

