

BI-METALLIC TEMPERATURE SWITCHES TYPE T084

Max voltage:	250 Vac
Current:	2 A @ 250 Vac 3 A @ 24 Vdc
Working temperature:	-30 ÷ 145 °C
Switching temperature:	30 ÷ 145 in step of 5 °C
Tolerance:	± 3,5 °C
Isteresis:	< 5 °C
Certification:	CE
Contacts:	Normally Open (O) Normally Closed (C)
Material:	Brass
Electrical Protection:	IP00 IP54 with CP54 Protection Cap
Mounting:	Sw 24



Rev.01/2021

ORDERING CODE

T084 T1 T3 T6 T7

TYPE	Temperature switches Sw 24
TEMPERATURE AVAILABLE	30 - 35 - 40 - 45 - 50 - 55 - 60 65 - 70 - 75 - 80 - 85 - 90 - 95 100 - 105 - 110 - 115 - 120 125 - 130 - 135
CONTACT	O (open) - C (closed)
CONNECTION	11 - 12 - 13 - 24 - 25 27 - 28 - 50
SPECIAL EXECUTION	00 - Standard

CODE EXPLANATION

TYPE

T084 Bi-Metallic Temperature Switches Sw 24

RANGE - T1

030	30 °C ± 5°C
035	35 °C ± 5°C
040	40 °C ± 5°C
045	45 °C ± 5°C
050	50 °C ± 5°C
055	55 °C ± 5°C
060	60 °C ± 5°C
065	65 °C ± 5°C
070	70 °C ± 5°C
075	75 °C ± 5°C
080	80 °C ± 5°C
085	85 °C ± 5°C
090	90 °C ± 5°C
095	95 °C ± 5°C
100	100 °C ± 5°C
105	105 °C ± 5°C
110	110 °C ± 5°C
115	115 °C ± 5°C
120	120 °C ± 5°C

CONTACT - T3

O Normally Open
C Normally Closed

CONNECTION Quote A - T6

11	G14"
12	3/8" BSPP L1=13,5 mm
13	1/2" BSPP L1=13,5 mm
24	M14 x 1.5 L1=13,5 mm
25	M22 x 1.5 L1=13,5 mm
27	M18 x 1,5 L1=13,5 mm
28	M16 x 1,5 L1=13,5 mm
50	5/8" UNF L1=13,5 mm

SPECIAL EXECUTION - T7

00 Standard
Special temperature range on request

