

## MAC3 Electromechanical level regulator



### Applications

The MAC3 level regulator is a float switch which allows electrical equipment to start and stop automatically (usually pumps, but also electric control valves, alarms, etc.) when a prefixed level has been reached. The most essential characteristic of this product is its high reliability and its shape which has no edges, for which it is particularly suitable for sewage water.

Also of great interest is the fact that it is made with a double liquid proof chamber which assures the maximum reliability of the inside mechanism.

### Models

Model	explain
MPM0506GB0C	SPDT, 5m cable
MPM1006GB0C	SPDT, 10m cable
MPM1506GB0C	SPDT, 15m cable

### Specifications

Microswitch electrical features	20(8)A 250V ~ , 16(4)A 250V ~
Approval certificates	ENEC/CE
External marking	10(8)A 250V ~ 10(4)A 250V ~
Operating temperature	0~50° C
Storage temperature	-20°C~80° C
Protection rating	IP 68
Switch angle	± 45°
Dimensions	106 x 154 x54mm
Weight	234g
Volume	384cm <sup>3</sup>
Max depth level	1 bar
Housing	Non-toxic polypropylene (PP)
Coloring	Non-toxic
Function class	I and II
cable standard	PVC 3X1 H07RN-F 3G1 H07BN4F 3G1 H07RNF 4G1 H07RNF 3X1 H07BN4F 3X1

Note: When ordering please specify if needed for filling or emptying function